

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) A gas generator (~~1~~, ~~46~~) comprising;

a squib (~~10~~) having a plug (~~24~~) having a header part (~~45~~) and two or more electrode pins (~~22~~, ~~23~~), and a thin-film bridge (~~25~~) having electrode pads (~~41~~, ~~42~~), wherein

the thin-film bridge (~~25~~) is activated to ignite ignition charge (~~26~~, ~~27~~), when an electric current is supplied to the thin-film bridge (~~25~~) via the electrode pins (~~22~~, ~~23~~), the gas generator wherein the thin-film bridge (~~25~~) of squib (~~10~~) is arranged into a hollow (~~32~~) prepared at the plug (~~24~~) in such a manner that the thin-film bridge (~~25~~) is kept approximately on a level with ~~the~~ a head (~~35~~) of the electrode pins (~~22~~, ~~23~~) and the header part (~~45~~) of the plug (~~24~~), the thin-film bridge (~~25~~) is connected by wire bonding to the electrode pins (~~22~~, ~~23~~) at the electrode ~~pads~~ ~~pad parts~~ (~~41~~, ~~42~~), and at least either of the electrode ~~pads~~ ~~pad~~ (~~41~~) ~~or~~ (~~42~~) of the thin-film bridge (~~25~~) is connected by the wire bonding to a metal part of the header part (~~45~~) of the plug (~~24~~).

2. (Currently Amended) The gas generator as set forth in claim 1 further comprising a housing (~~4~~) with at least two ends having therein a combustion chamber (~~6~~) in which gas generants (~~5~~) generating a high temperature gas by burning are sealed and a filter chamber (~~8~~) to which a filter member (~~7~~) is attached, wherein the gas generants (~~5~~) inside the combustion chamber (~~6~~) are ignited and burnt by the squib (~~10~~).

3. (Currently Amended) The gas generator as set forth in claim 2, wherein the housing (~~4~~) is 30 mm or less in an outer diameter and the squib (~~10~~) is attached to the one end (~~3~~) of the housing (~~4~~).

4. (Currently Amended) The gas generator as set forth in claim 2 or claim 3, wherein the housing (4) is in a closed-end cylindrical shape, which is opened at the one end (3) and closed at the other end (2).
5. (Currently Amended) The gas generator as set forth in claim 2 or claim 3, which is provided with a first partition member (9) dividing the combustion chamber (6) and the filter chamber (8).
6. (Currently Amended) The gas generator as set forth in claim 2 or claim 3, wherein the other end (2) of the housing (4) is in a bowl shape or in a flat-bottomed shape.
7. (Currently Amended) The gas generator as set forth in claim 2 or claim 3, wherein propellant (14) is sealed inside the combustion chamber (6).
8. (Currently Amended) The gas generator as set forth in claim 7; wherein the gas generants (5) and the propellant (14) are not loaded into a container but directly sealed into the combustion chamber (6), and the gas generants (5) and the propellant (14) are divided by a second partition member (47).
9. (Currently Amended) The gas generator as set forth in claim 5, wherein the first partition member (9) is crimped and fitted into the housing (4) from the outer peripheral end surface thereof.

10. (Currently Amended) The gas generator as set forth in claim 1, further comprising:
a gas cylinder (~~51~~) having therein a compressed gas,
a housing (~~54~~) in which a propellant (~~52~~) and the squib (~~10~~) are housed,
an outer cylindrical member (~~55~~) connecting the gas cylinder (~~51~~) to the housing (~~54~~)
and holding them, wherein
the gas cylinder (~~51~~) having a rupture disk (~~66~~) for retaining the pressure and sealing
the compressed gas at the end of it facing the housing (~~54~~),
the outer cylindrical member (~~55~~) having a filter member (~~57~~) mounted along the an
inner periphery of the outer cylindrical member (~~55~~), and
a gas retaining space (~~59~~) is formed between the gas cylinder (~~51~~) inside the outer
cylindrical member (~~55~~) and the housing (~~54~~).

11. (Currently Amended) The gas generator as set forth in claim 10, wherein the gas cylinder
(~~51~~) is in the range from 20 mm to 30 mm in outer diameter.

12. (Currently Amended) The gas generator as set forth in claim 10 or claim 11, wherein the
rupture disk (~~66~~) is ruptured by a force of flames from the squib (~~10~~).

13. (Currently Amended) The gas generator as set forth in claim 10 or claim 11, wherein a
plurality of ~~second~~ flame discharging openings (~~60~~) toward the outer cylindrical member (~~55~~)
are formed at a side cylindrical part (~~68~~) on the a bottom (~~67~~) of the housing (~~54~~).

14. (Currently Amended) The gas generator as set forth in any one of claims 1, 2, 3, 8, 9, 10,
or 11, wherein the surface of the electrode pads (~~41 and 42~~) are made of any one of gold,
aluminum, nickel or titanium.

15. (Currently Amended) The gas generator as set forth in any one of claims 1, 2, 3, 8, 9, 10, or 11, wherein a wire ~~(28)~~ used in wire bonding is made of gold or aluminum and the wire ~~(28)~~ is in the range from 10 μm to 500 μm in diameter.

16. (Currently Amended) The gas generator as set forth in any one of claims 1, 2, 3, 8, 9, 10, or 11, wherein the wire ~~(28)~~ used in the wire bonding is 1 mm or less in loop height ~~(h3)~~.